



Applications

- Self-drilling, double anchorage fixing for plasterboard: thickness 10 to 13 mm with or without insulation (polystyrene, etc...)
- Bathroom accessories
- Kitchen cabinets
- Radiators, electrical enclosures

Material

- Anchor body-zamak 3, NFA 55.010
- Special screw supplied, head type PZ2

Special fixing for plasterboard: double anchorage

Technical data

TYPE	Max thick of part to be fixed (mm)	Ø thread (mm)	Ø anchor head (mm)	Ø screw head (mm)	Screw length (mm)	Total anchor length (mm)	Eurocode
	t_{fix}	d	-	D	$L1$	L	
TP 12	12	4,5	16	9,2	45	39	061190
TF 30	30	4,5	16	8,8	60	39	061200

TP = Pan head TF = Countersunk head

Recommended and ultimate loads (kN)

TENSILE kN



OBLIQUE kN



SHEAR kN



TYPE	Plasterboard BA 10		Plasterboard BA 13	
	N_{rec}	$N_{u,m}$	N_{rec}	$N_{u,m}$
TP12	0,084	0,42	0,12	0,60
TF30				

TYPE	Plasterboard BA 10		Plasterboard BA 13	
	V_{rec}	$V_{u,m}$	V_{rec}	$V_{u,m}$
TP12	0,23	1,15	0,28	1,40
TF30				