

Paslode Nails

Finish: **Hot Dipped Galvanized**

Nail type: **2.5mm diameter ring shank**



For **30° Tools**

DIAMETER	• 2.5
SHANK	• Ring
FINISHES	• Hot Dipped Galvanized + Paint
COLLATION	• Plastic collated strip nails
TOOLS	• PSN90 • PSN100 • IM350 • IM90i

MATERIAL PROPERTIES





- **Tensile strength wire:**
minimum 700 N/mm²
- **Shank diameter (ds)¹:**
2.50 mm
- **Profile diameter minimum (dp):**
2.63 mm
- **Head diameter (D)²:**
5.85 mm
- **Length Range (LT)¹:**
50 mm
- **Number of nails:**
26 nails per strip

Coil Nails Full Head ring



INTENDED USE - CORROSION PROTECTION

- Wood to wood 

Finishes	Eurocode 5 Service class	Label colour on packaging
Hot Dipped Galvanized Minimum 55 microns of zinc B = + Black paint R = + Red paint	Service Class 1 Indoor use 	Red 
	Service Class 2 Outdoor protected use 	
	Service Class 3 Outdoor use 	

CHARACTERISTIC PARAMETERS

“Calculated or tested according to EUROCODE 5”

If necessary, nails can be tested in order to define values

NAIL LENGTHS**

Diam.	Length in mm (LT)	Code for PSN90 / PSN100 ³	Code for IM350 ³	Code for IM90i ³
2.5	50	114819B	141200B	142000B
2.5	50	114818R	141237R	142001R

** In order to select the correct nail length for a given connection please always consult standards and good practice on your local market. Please see appendix for an example of national guidelines

¹ Tolerance according to EN10218-2 for wire diameter and according to EN14592 for the nail length

² Tolerance ± 0.3 mm

³ Please check availability of the reference in the Product Catalogue